

OZONE HW-VT01/2

UTP Video Balun

OSMOSIS IRELAND LTD, UNIT 30 CLONSHAUGH BUSINESS & TECHNOLOGY PARK, CLONSHAUGH, DUBLIN 17
 TEL: 01 852 3600 FAX: 01 852 3625 EMAIL: SECURITY@OSMOSIS.IE WEB: WWW.OZONECCTV.IE

Features:

Compatible with PAL、NTSC、SECAM system
 Brightness of video adjustable,
 Real time video transmit,
 Transmits Video 350m
 Built in Surge Protector& Noise Filter
 No Need to Hassle with Screw Terminals
 Provides a Highly Cost Effective Solution
 Huge Savings on Cabling Costs



Simple type (≤350m)
HW-VT01/2

OZONE HW-VT01/2	Item No	HW-VT01/2
	Normal output Level	1Vp-p/75 ohms
	Bandwidth	Video: 0~10MHZ/3dB
	Differentiation Gain	<2%
	Differentiation Phase	<2%
	S/N Ratio:	60dB
	Insertion Loss	Less than 60dB per pair over the frequency range from 0~10MHZ
	Wire type	Unshielded Twisted pair: 24AWG UTP CAT-5
	Transmit distance	≤ 350m(color)
	UTP Impedance:	100±20 ohm
	Common Mode Rejection	≤18 Ω/100m@AWG24(recommend:30 Ω/305m)
	Distributed Capacitance	<62PF/m
	Working temperature	-30℃~85℃
	Storage temperature	-40℃~85℃
	Opposite humidity	0~95%
	System	NTSC , PAL, SECAM , CCHIR
Power	No	
Strong ability of anti-interference	6000V 1.2uS×50uS 3000v 8uS connect with grounding	