

OSMOSIS LCD Monitors 15", 17" & 19"

Graceful, Solid...



KS-ML1525

- 15" Multi-inputs LCD monitor
- Fast response time at 16ms
- High contrast ratio at 500:1
- High brightness at 225 cd/m²
- Support multiple language selections
- Selectable color temperature under PC mode
- Sleep timer definable for users
- 2D comb filter and 2D de-interlace



KS-ML1725 / KS-ML1925

- 17" /19" Multi-inputs LCD monitor
- Fast response time at 16ms
- High contrast ratio at 500:1
- High brightness at 290 cd/m² (ML1725)
250 cd/m² (ML1925)
- Support multiple language selections
- Selectable color temperature under PC mode
- Sleep timer definable for users
- 2D comb filter and 2D de-interlace

15" / 17" / 19" LCD Monitor

For More Details or Pricing:

Email: security@osmosis.ie Tel: 01 852 3600



LCD Monitors 15", 17" & 19"



Model	KS-ML1525	KS-ML1725	KS-ML1925
Front Control	Menu, VOL-, VOL+, Source, Power	Menu, VOL-, VOL+, Source, Power	Menu, VOL-, VOL+, Source, Power
Display Resolution (Dot)	640x480@60/72/75, 800x600@60/72/75, 1024x768@60/70/75	640x480@60/72/75, 800x600@60/72/75, 1024x768@60/70/75 1280 x 1024@60/75	640x480@60/72/75, 800x600@60/72/75, 1024x768@60/70/75 1280 x 1024@60/75
Active Area (mm)	304.128(H)x228.096(V)	337.920(H)x270.336(V)	376.32(H)x301.06(V)
Dot Pitch (mm)	0.297x0.297mm	0.264x0.264mm	0.294x0.294mm
LCD Profile Ratio	4:3	5:4	5:4
Display Color	16.2M	16.2M	16.2M
Brightness (Central)	225cd/m ²	290cd/m ²	250cd/m ²
Contrast Ratio	500:1	500:1	500:1
Viewing Angle	70 (Left) / 70 (Right) 60 (Up) / 60 (Down)	70 (Left) / 70 (Right) 63 (Up) / 67 (Down)	70 (Left) / 70 (Right) 65 (Up) / 60 (Down)
Response Time	16ms	12ms	16ms
Input AC Voltage	AC 100~240V 60Hz/50Hz	AC 100~240V 60Hz/50Hz	AC 100~240V 60Hz/50Hz
Input DC Adaptor	DC12V / 3.15A	DC12V / 3.15A	DC12V / 4.16A
Input Signal	1 Vp-p Composite Video	1Vp-p Composite Video	1Vp-p Composite Video
Input Impedance	75 ohm	75 ohm	75 ohm
Operating System			
NTSC	525 Lines, 60 fields / sec.	525 Lines, 60 fields / sec.	525 Lines, 60 fields / sec.
PAL	625 Lines, 50 fields / sec.	625 Lines, 50 fields / sec.	625 Lines, 50 fields / sec.
Connector			
VGA Input	15 PIN D-SUB Connector	15 PIN D-SUB Connector	15 PIN D-SUB Connector
PC Audio Input (L/R)	Ear Phone Jack Input x 1	Ear Phone Jack Input x 1	Ear Phone Jack Input x 1
Video Input / Output	BNC In x 1, BNC Out x1	BNC In x 1, BNC Out x1	BNC In x 1, BNC Out x1
Audio Input (L/R)	RCA In x 1 set	RCA In x 1 set	RCA In x 1 set
S-Video Input	4 PIN DIN Connector x 1	4 PIN DIN Connector x 1	4 PIN DIN Connector x 1
Speaker	1W+1W	1W+1W	2W+2W
Audio Output (L/R)	RCA Output x 1	RCA Output x 1	RCA Output x 1
Power Consumption	25W	35W	45W
Weight	N.W./G.W.: 4KG / 4.5KG	N.W./G.W.: 4.5 / 5.0KG	N.W./G.W.: 5KG/5.5KG
Dimension	378(W) x 191(D) x 312(H)mm	370(W) x 191(D) x 324(H)mm	419.5(W) x 191(D) x 368(H)mm
Operating Temperature	0~50°C	0~50°C	0~50°C
Storage Temperature	-20~60°C	-20~60°C	-20~60°C
Certificate	FCC CE	FCC CE	FCC CE

Specifications subject to change without notice.

Osmosis Ireland Ltd. Unit 30 Clonshaugh Business & Technology Park, Clonshaugh, Dublin 17
 tel: 01 852 3600 email: security@osmosis.ie web: www.osmosis.ie